

SPECIFICATIONS

General	
Frequency	446 - 446.2 MHz
Channel Capacity	16 channels
Power Supply	7.4V DC
Dimensions	135mm x 55mm x 27mm
Weight	168g
Operating Temp	-20°C to +60°C
Battery Capacity	3000mAh; Li-ion

Transmitter	
RF Power	0.5W
Channel Spacing	12.5 kHz
Frequency Stability	±1.5ppm
Modulation Deviation	≤2.5kHz / ≤5kHz
Spurious & Harmonics	-36dBm <1Ghz, -30dBm >1Ghz
FM Hum & Noise	≤-40dB / ≤+40dB
Adjacent Channel Power	≥60dB / 70dB
Audio Response (300-3000Hz)	+3dB - 3dB
Audio Distortion (300-3000Hz)	≤5%

Receiver	
Sensitivity (12dB SINAD)	≤0.25μv / ≤0.35μv
Adjacent Channel Selectivity	-60dB / -70dB
Audio Output @ <5% Distortion	1W
Audio Distortion	≤5%
Radiated Spurious Emissions	-54dBm
Intermodulation Rejection	-70dB
Spurious Response	65dB



Battery



Charging Base



Antenna



Belt Clip

WAVLINK®

WAVLINK V-732

Professional Two-Way Radio



Durable
Antenna



Emergency
Alarm



3000mAh
Battery



VOICE
Scrambler



RELIABLE RANGE, EVERYWHERE YOU GO.

WavLink V-732 Professional Two-Way Radio

